

Canon imageRUNNER 2520



Basic Specifications

Type

Desktop or Free-standing, (Reader-Printer Combined)

Maximum Original Size

A3

Copy Sizes

Cassette 1,3 and 4: A3, A4, A4R, A5R

Custom size: 139.7 to 297mm x 182 to 432mm

Cassette 2: A3, A4, A4R, A5R, Envelope (with optional Envelope Feeder Attachment-D1)

Stack Bypass: A3, A4, A4R, A5R, Envelopes

Custom size: 99 to 297mm x 148 to 432 mm

Resolution

Reading: 600dpi × 600dpi

Copying: 600dpi × 600dpi

Printing: 600dpi × 600dpi, 1200dpi x 1200dpi (UFR11-LT only)

Number of Tones: 256 Gradations

Copy/Print Speed

A4:

imageRUNNER 2545i/2545 : 45ppm (BW)
imageRUNNER 2535i/2535 : 35ppm (BW)
imageRUNNER 2530i/2530 : 30ppm (BW)
imageRUNNER 2525i/2525 : 25ppm (BW)
imageRUNNER 2520i/2520 : 20ppm (BW)

A3:

imageRUNNER 2545i/2545 : 22ppm (BW)
imageRUNNER 2535i/2535 : 22ppm (BW)
imageRUNNER 2530i/2530 : 15ppm (BW)
imageRUNNER 2525i/2525 : 15ppm (BW)
imageRUNNER 2520i/2520 : 15ppm (BW)

Magnification

Zoom: 25-400%

Fixed: 25%, 50%, 70%, 100%, 141%, 200%, 400%

First Copy Time

Black-and-White: 3.9sec (45/35 ppm model), 5.4sec (30/25 ppm model), 6.4sec (20 ppm model)

Warm-Up Time

30 seconds

Multiple Copies/Prints

1 to 999 sheets

Duplexing

Standard

Paper Weight

Cassette: 64 to 90g/m²

Stack Bypass: 64 to 128g/m²

Duplex: 64 to 80g/m²

Cassette

Paper Capacity

Cassette 1: 550 sheets (80g/m²), (250 sheets for the imageRUNNER 2520i/ 2520)

Cassette 2: 550 sheets for imageRUNNER 2525/i, 2530/i, 2535/i, 2545/i. 50 envelopes (with optional Envelope Feeder Attachment-D1)

Stack Bypass: 100 sheets (A4,A4R,A5;80g/m²), 50 sheets(A3;80g/m²)

Optional:

550 sheets x 2 cassettes (80g/m²)

550 sheets x 1 cassette for imageRUNNER 2520/2520i only

Paper Deck: None

Total capacity: 2,300 sheets,(2,000 sheets for the imageRUNNER 2520i/ 2520)

CPU

Canon Custom Processor, 400MHz

Memory

512MB (imageRUNNER 2500 i models), 256MB (imageRUNNER 2500 non i models)

Hard Disk Drive

None

Interface

Ethernet (100Base-TX/10Base-T), USB Host I/F 2.0 x 1 port, USB Device 1.0 x 1 port

Power Supply

220-240V AC, 50/60Hz, 4.2A (45/35 ppm model), 220-240V AC, 50/60Hz, 3.3A (30/25/20 ppm model)

Power Consumption

1.827kW (45/35ppm model), 1.345kW (30/25ppm), 1.542kW (20ppm model)
Lot26 (http://www.canon-europe.com/For_Work/Lot26/index.aspx)

Dimensions

imageRUNNER 2545i/ 2545/ 2535i/ 2535 :
565 mm x 680 mm x 806 mm (with the platen cover)
565 mm x 689 mm x 907mm (with the DADF)
imageRUNNER 2530i/ 2530/ 2525i/ 2525 :
565 mm x 680 mm x 806 mm (with the platen cover)
565 mm x 689 mm x 896 mm (with the DADF)
imageRUNNER 2520i/ 2520 :
565 mm x 680 mm x 681 mm (with the platen cover)
565 mm x 689 mm x 771 mm (with the DADF)

Weight

imageRUNNER 2545i/2535i :
Approx. 78.4 kg, imageRUNNER 2545/2535: Approx. 70.5 kg
imageRUNNER 2530i/2525i :
Approx. 77.5 kg, imageRUNNER 2530/2525: Approx. 68.0 kg
imageRUNNER 2520i :
Approx. 56.0 kg, imageRUNNER 2520: Approx. 50.5 kg

Model Name**PDL**

UFR II-LT, PCL5e/6 (standard on i models, optional on non i models), PostScript level 3 emulation (optional)

Resolution

600 x 600dpi, 1200dpi x 1200dpi (UFR II-LT only)

Memory

512MB (imageRUNNER 2500 series i models), 256MB (imageRUNNER 2500 series non i models)

Hard Disk

None

CPU

Canon Custom Processor, 400MHz

PS Fonts

Roman 136

PCL Fonts

Roman 93

Supported OS

PCL: Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7

Postscript level 3 emulation: Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7, Mac OS X (10.4 or later)

UFRII-LT: Windows 2000/ XP/ Server 2003/ Vista/ Server 2008/ Windows 7, Mac OS X (10.4 or later), Linux

Mac-PPD: Mac OS X 10.4 or later

Interface

Ethernet (100Base-TX/10Base-T)

Network Protocol

TCP/IP(LPD/ Port9100, HTTP), SMB, SNMP v1, WSD, IPv4/ IPv6 support

Pull Scan

Network TWAIN Driver (75/ 100/ 150/ 200/ 300dpi 8bit color / 75-600dpi 1bit Black & white)

Universal Send Kit**Optional/Standard**

CLR SEND KIT-Y1 (standard on i models, optional on non i models)

Model Name**Scan speed**

A4, 300dpi, BW/Color: 45/34 ipm (45/ 35 ppm model), 25/13ipm(30/ 25/ 20 ppm model)

Scan Resolution

BW: 100 x 100 dpi, 150 x 150 dpi, 200 x 100dpi, 200 x 200 dpi, 200 x 400 dpi, 300 x 300 dpi, 400 x 400 dpi, 600 x 600 dpi

CL:100 x 100 dpi,150 x 150 dpi, 200 x 200 dpi, 300 x 300dpi

Destinations

E-Mail/ Internet FAX(SMTP), PC/Server (SMB,FTP), USB memory key

Address Book

Local (Max. 500)

File Format

TIFF, JPEG, PDF, High compression PDF
Searchable PDF (optional with SEARCHABLE PDF-C1)

DADF

Optional/Standard

DADF-AA1 optional for imageRUNNER 2545/2535, standard for imageRUNNER 2545i/2535i.

DADF-AB1 optional for imageRUNNER 2530/2525/2520, standard for imageRUNNER 2530i/2525i/2520i

Model Name

Paper Size

imageRUNNER 2545/2535: A3, A4, A4R, A5, A5R

imageRUNNER 2530/2525/2520: A3, A4, A4R, A5, A5R

Custom size 139.7 to 297mm x 182 to 432mm

Paper Weight

imageRUNNER 2545/2535:

Single sided original: 42 to 128 g/m²

Double sided original: 50 to 128 g/m²

imageRUNNER 2530/2525/2520:

Single sided original: 37 to 128 g/m²

Double sided original: 50 to 128 g/m²

Max. Number of Originals

imageRUNNER 2545/2535:

100 sheets (A4, A4R, A5, A5R: 80 g/m²), 50 sheets (A3: 80 g/m²)

imageRUNNER 2530/2525/2520:

50 sheets (A4, A4R, A5, A5R: 80 g/m²), 25 sheets (A3: 80 g/m²)

Document Scanning Speed

imageRUNNER 2545/2535:

Copy: 45ipm (A4, 600 x 600 dpi: BW)

Scan: 45/34 ipm (A4, 600 x 600 dpi: BW / 300 x 300 dpi: Colour)

imageRUNNER 2530/2525/2520:

Copy: 25ipm (A4, 600 x 600 dpi: BW)

Scan: 25/13 ipm (A4, 600 x 600 dpi:BW / 300 x 300 dpi: Colour)

Dimensions

imageRUNNER 2545/2535: 565 mm x 540 mm x 137 mm

imageRUNNER 2530/2525/2520: 565 mm x 544 mm x 126 mm

Weight

imageRUNNER 2545/2535: Approx. 7.9 kg

imageRUNNER 2530/2525/2520: Approx. 7.0 kg

cassette Feeding Module**Model Name**

CASSETTE UNIT-W1 for imageRUNNER 2520/i

CST. Feeding UNIT-AE1 for all models

Type

CASSETTE UNIT-W1: Front-loading adjustable drawers

CST. Feeding UNIT-AE1: 2 Front-loading adjustable drawers

Paper Weight

CASSETTE UNIT-W1: 64 to 90g/m²

CST. Feeding UNIT-AE1: 64 to 90 g/m²

Paper Capacity

CASSETTE UNIT-W1: 550 sheets (80 g/m²) x 1 cassette

CST. Feeding UNIT-AE1: 550 sheets(80 g/m²) x 2 cassettes

Dimensions (W x D x H)

CASSETTE UNIT-W1: 565 mm x 680 mm x 97 mm

CST. Feeding UNIT-AE1: 565 mm x 680 mm x 248 mm

Weight

CASSETTE UNIT-W1: Approx. 12.8kg

CST. Feeding UNIT-AE1: Approx. 24.0kg

Finisher**Optional/Standard**

Optional Inner Finisher-B1 for all models

Model Name**Number of Trays**

One stack tray (Optional 2nd Tray;INNER FIN ADD. TRAY-B1)

Tray Capacity

A4 - A5R :1000 sheets (or 125 mm in height)

A3, A4R: 500 sheets (or 62.5 mm in height)

Staple Position

Corner, Double

Staple Capacity

A4: 50 sheets x 30 sets

A4R/ A3: 30 sheets x 15 sets

Model Name

Tray Capacity

Tray A - A4: 250 sheets, A3: 100 sheets

Tray B - A4:100 sheets, A3: 50 sheets

Weight

Approx. 0.6kg

Other Accessories

Other Accessories (Optional)

Platen Cover Type P: Platen cover to be selected when configuring imageRUNNER 2525/2530 without DADF

Platen Cover Type Q: Platen cover to be selected when configuring imageRUNNER 2535/2545 without DADF

Stamp Ink Cartridge-C1: Stamp Ink Cartridge

Stamp unit-B1: Stamp Unit

ADF Access Handle-A1:Attaches to the document feeder, making access easier for seated users

PCL Printer Kit-AF1: Supports PCL5e and PCL6 printing for non-i Models

PS Printer Kit-AF1: Supports PostScript Level 3 Emulation printing

Barcode Printing Kit-B1: Provides Barcode printing capability using Jet Caps technology

Super G3 Fax Board-AG1: Add fax functionality

FL Cassette-AJ1: This spare 550-sheet tray for cassette "1" of imageRUNNER

2525/2525i/2530/3530i/2535/2535i/2545/2545i

FL Cassette-AK1: This spare 550-sheet tray for cassette "2" of imageRUNNER

2525/2525i/2530/3530i/2535/2535i/2545/2545i

or for Cassette Feeding Unit-AE1 or Cassette Module-W1 allows you to swap paper sizes without changing the printer settings

FL Cassette-AL1: This spare 250-sheet tray for cassette "1" of imageRUNNER 2520/2520i

allows you to swap paper sizes without changing the printer settings

Cassette Spacer-A1: Adjusts the height for 250-sheet cassette when combined with optional

Cassette Feeding Unit-AE1 or Cassette Module-W1 on imageRUNNER 2520/2520i only

Envelope Feeder Attachment-D1: Attaches to cassette "2" for easy envelope feeding

imageRUNNER 2500 Plain Pedestal: The pedestal substitutes for the cassette feeding unit and raises the device,

2 Way Unit-B1: Enhances the double-sided print productivity up to 100%

Reversal Pass Unit(2-Way Unit) option for imageRUNNER 2520/2520i/2525/2530

Staple-J1:Staples for Inner Finisher-B1

Document Tray-J1: Handy tray that attaches to the side of the device and provides a location for placing originals

Power Supply Unit-U1: Power Supply Unit.

Card Reader Attachment-D3: Attachment kit for Card Reader-F1

Canon Card Reader-F1: Physical card access system that limits system access to authorised users

USB Application 3-Port Interface Kit-A1: 3-Port USB interface kit for USB memory

CCVI I/F Cable-A1: Interface Kit for Coin-Vender

C-EXV33 TONER BK: Toner for imageRUNNER 2520/2520i/2525/2525i/2530/2530i

C-EXV32 TONER BK: Toner for imageRUNNER 2535/2535i/2545/2545i