
S	SHEET LIST
G100	COVER
G200	NOTES
G300	THREE DIMENSION
A100	FLOOR PLAN STRUCTURAL
A200	FLOOR PLAN ARCHUITECTURAL
A300	END ELEVATIONS
A400	END ELEVATIONS LEFT AND RIGHT
A500	END ELEVATIONS
A600	ROOF CROSS SECTION DETAILS
A700	ROOF PLAN
A800	WALL SECTIONAL DETAILS
A900	FOUNDATION DETAILS
A101	STEEL SECTION U-SHAPE

DRAWINGS AND SPECIFICATIONS

TEMPORARY LEARNING SPACE CLASSROOM BLOCKS CONSTRUCTION

All Region - Access via State HQs Coordinates: TBD

> FUNDED BY: GLOBAL PARTNERSHIP FOR EDUCATION



SITE PREPARATION

- Building Site to be graded flat with 5% slope away from structure, extending a minimum of 2.5M from perimeter •
- Drainage necessary away from structure, which may require substantial fill material

CONCRETE

- River sand may be used only after thorough washing to remove fines (silt and clay) •
- All aggregate to be clean and free of organic material •
- Water to be clear use flocculent on river water or any water with suspended particles •

FOUNDATIONS COLUMN EXCAVATION

- 400mm x 400mm x 900mm mass concrete pad foundation under each foundation steel column •
- Concrete to be 1:2:4 cement:sand:aggregate , for the footing concrete ٠
- All aggregate to be <50mm •

FOUNDATION COLUMNS FOOTINGS

- 100mm x 100mm x 3mm fixed at the depth of 600mm, fdn. column with a
- Concrete to be 1:2:4 cement:sand: aggregate , for foundation column base ٠

All aggregate to be <50mm

SLAB

- 75mm thick reinforced concrete floor slab 1:2:4 concrete and for location • without murram; compact normal soil and sand compacted before slab to reduce the compression and expansion.
- Floor slab to be with floor screed monolithically to achieve uniform bond. •
- Control joints to be located between all rooms. Joint can be insert or saw cut, 10mm minimum depth •

WALL COLUMNS:

- 100mm x 100mm x 3mm thick steel hollow wall section reinforced with •
- Concrete to be 1:2:4 cement:sand:aggregate, for wall column Build half wall with brick walls, ٠

WALLS:

NOTE: for locations without clay burnt bricks, use of local materials like Bamboos, Timbers boards, and iron sheets can be • used for the walls

- 400mm high from foundation use brick work to prevent flooding, ٠
- 1800mm Bamboo walling on front and rear face of the building •
- 2800mm high from the foundation and finished with iron sheets •

NOTE: For locations without murram; use the available black cotton soil, mixed with sand and compact. spread a layer of sand on top of the compacted ground and then cast the flor slab.

	TITTLE:	Phase 01	Sheet_#	INDEX	REVISION	DATE	PROJECT:	
		Date	C200	1_IN	NOTES	14.10.2020		
	PROPOSED_ILS	DATE	9200	2_IN	2_REVISION	2_00.00.09		
		Scale Format 1:100 A3		3_IN	3_REVISION	3_00.00.09	APPROVED_BY:	
unicef	DESIGN:	Filename CONSTRUCTIO	N-CLASSROOM_BK-2021.DWG	6 4_IN	4_REVISION	4_00.00.09		
unicer	UNICEF_SOUTH_SUDAN	Project Manager EDU/UNICEF/SS	Drg. By: AW	5_IN	5_REVISION	5_00.00.09		

DOORS

- All doors are made of Iron sheets **ROOF Metallic**
- Use corrugated 28gauge colored roof sheet •

three coats of anti rust paint or equivalent

• and connection

• minimum 6mm thickness as indicated on drawings

- Rafters structure members to all be welded with adequate weld fillet of at least 6mm • Roof structure /tie beam to be welded to 60mm x 40mm square tube. •
- Roof sheets profile to be corrugated colored, 28 gauge •
- All sheets to overlap 200mm

FLOOR

- Concrete floor to be 75mm 1:2:4 cement:sand: aggregate ٠
- Floor screed monolithically to achieve uniform bond.
- Compact murram, or place hardcore or compact natural soil mixed with sand to attain maximum compacted base layer. All Floor style may vary according to the location.


Type of	Mi	х.	proport	ions	Dry required quantities for one cubic meter wet: Cement Stones or							
Cement Work	Cement	:	Sand	Gravel	bags @ 50 kg	kg	Sand [m ³]	Gravel [m ³]	Boulders [m ³]			
	1	:	1	-	20.4	1020	0.71	-	-			
	1	:	2	-	13.6	680	0.95	~	-			
Cement	1	:	3	-	10.2	510	1.05	-				
Mortars	1		4	-	7.6	380	1.05	-	-			
	1	:	6	-	5.0	250	1.05	~	~			
Cement												
Plaster	1	:	4	-	0.18	9	0.024	-	-			
20 mm w/ 2% waste)	1	:	6	-	0.12	6	0.024	-	-			
	1	:	4	uncoursed stone	2.66	133	0.37	2	1.2			
Stone	1	:	6	masonry	1.75	87.5	0.37	2	1.2			
asonries	1	:	4	coursed stone	2.28	114	0.32	-	1.25			
	1	:	6	masonry	1.50	75	0.32	-	1.25			
	1	:	4	: 8	3.4	170	0.47	0.94	-			
Cement	1	:	3	: 6 (M10)	4.4	220	0.46	0.92	-			
(plain or Einforced)	1	:	2	: 4 (M15)	6.4	320	0.45	0.90	-			
	1	;		: 3 (M20)	8	400	0.42	0.84	-			
"Plum"	1	:	3 0% bou	: 6	2.64	132	0.28	0.54	0.50			

- All 60mm x 40mm x 1.5mm rafters, 60mm x40mm Tei Beam, 40mm x 40mm x 1.5mm struts and 40mm x 40mm x 1.5mm square steel purlins. All members to painted with
 - Purlins to be weld to rafter and to supporting cleat to provide adequate weld area
 - All steel members to be free of rust and all Nodes to connected with gusset plate of

FUNDED_BY:				
APPROVED_BY	S/No.	NAME:	Date:	SIGNATURE:
-	01			
	02			
INVESTICY OF PHYSICAL INFRASTRUCTURE	03			



	TITTLE:	01	Silou_#	INDEX	REVISION	DATE	PROJECT:	
			~ 200	1_IN	DRAWINGS:_PLAN_ELVEATION_SECTIONS_ROOFPLAN	14.10.2020		
NS N	PROPOSED NEW	DATE	G200	2_IN	2_REVISION	2_00.00.09		
		Scale Format 1:100 A3		3_IN	3_REVISION	3_00.00.09	APPROVED_BY:	
unicef	DESIGN:	Filename NEW-CLASSROOI		4_IN	4_REVISION	4_00.00.09		
unicer	UNICEF_SOUTH_SUDAN	Project Manager EDU/UNICEF/SSD	Project Owner 2020/EDUC/SSD	5_IN	5_REVISION	5_00.00.09		



UNICEF_SOUTH_SUDAN


Project Manager EDU/UNICEF/SSD

Drg. B AW

5_IN

5_REVISION

5_00.00.09



UNICEF_SOUTH_SUDAN


Project Manager EDU/UNICEF/SSD

DESIGN


unicef


3_IN 3_REVISION 3_00.00.09 Filename SCHOOLS-CLASSROOM_BK-2021.DWG 4_IN 4_REVISION 4_00.00.09 Drg by AW 5_IN 5_00.00.09 5_REVISION

FUNDED_BY:			
APPROVED_BY	S/No.	NAME:	Date:
	01		
(America)	02		
INVESTION OF REVISIONAL INFRASTRUCTURE			




FUNDED_BY:			
APPROVED_BY	S/No.	NAME:	Date:
	02		





FUNDED_BY:			
APPROVED_BY	S/No.	NAME:	Date:
	02		
INVESTITY OF PRIMECAL INFRASTRUCTURE			



5_00.00.09

unicet

UNICEF_SOUTH_SUDAN


Project Manager EDU/UNICEF/SSD


Project Owner 2021/EDUC/SSD

5_IN


5_REVISION

FUNDED_BY:				
APPROVED_BY	S/No.	NAME:	Date:	SIGNATURE:
	01			
(And)	02			
INSTRY OF REMSCAL INFRASTRUCTURE	03			





FUNDED_BY:				
APPROVED_BY	S/No.	NAME:	Date:	SIGNATURE:
		TO UNE.	Date.	DIGINATORE.
	01			
	02			
INSERT OF PHYSICAL INFRASTRUCTURE	03			



	TITTLE:	01	eet_#	INDEX	REVISION	DATE	PROJECT:	FUNDED_BY:		
			٨٩٩٩	1_IN	DRAWINGS:_FOUNDATION_FOOTINGS	14.10.2020				
	PROPOSED TLS		A900	2_IN	2_REVISION	2_00.00.09				
	—	Scale Format 1:100 A3		3_IN	3_REVISION	3_00.00.09	APPROVED_BY:	APPROVED_BY'	NAME:	Date:
unicof	DESIGN:	Filename SCHOOLS-ADMINIS	STRATION_BK-2020.DWG	4_IN	4_REVISION	4_00.00.09	-			
unicef	UNICEF_SOUTH_SUDAN	Project Manager EDU/UNICEF/SSD	Project Owner 2020/EDUC/SSD	5_IN	5_REVISION	5_00.00.09				