

Center for International Programs
ICAP in South Sudan
Purchase Requisition

Date_13th July 2021 _____

Requesting Department _Technical Office _____

Please purchase the following items for:

C] Main Office Supported ICAP Site(s) (Please List)


Grant Number: GG014355- 02 _____

Attach distribution

Item No.	Descri tion of materials	Account Number	Units Measures	QTY	Remark
	Honda XL125, on and off road white in color 2013 Model, Technical specifications: Engine Single-cylinder, air-cooled, 4-stroke, OHC. Displacement 124.73 cc. Max. Power 8.0 kW/8,250 rpm. Max. Torque 10.4 Nm/6,5()O rpm. Bore x Stroke 52.4 mm x 57.9 mm. Compression Ratio 9.2: 1 Air Filter Type Paper Element (Vixcous Type). Starting Method Electric/Kick. Ignition DC-CDI Battery Transmission 5-speed, Manual, I-N-2-3-4-5. Dimension (L x W X H) 2,107 x 827 x 1,125 mm Wheelbase 1,358 mm. Seat height 849 mm. Ground Clearance 263 mm. Kerb weight 127 kg. Fuel Tank Capacity12.() L. Battery 12V-4Ah. Head Lamp 12V-35/35W. Tire size Front:70/100-21, Rear: 100/90-18. Brake Front/Rear: Leading Trailing Drum. Frame Type Semi Double Cradle. Front Suspension Telescopic Fork, 159mm Axle Travel. Rear Suspension High Density Rear Shock Tube, 148mm Axel Travel		Piece	20	
2	Helmed, white with ICAP 10 0		iece	20	
3	Box carrier with ICAP 10 0		iece	20	

4	<p>Biscycle Princes Severange classic Colours Buckingham Black or Regency Green Gears Sturmey Archer 5 speed hub gear (RXRD-5) with thumb shifter control, Frame Traditionally lugged and brazed hand-crafted steel frame. Fork Tubular crown, hand-brazed, Saddle Antique brown Brooks B66s natural leather saddle with twin coil springs. Handlebar Chrome plated raised bar, with authentic black rubber grips, on an alloy and stainless steel stem. Brakes All-weather, low maintenance front and rear hub brakes, Wheels 26" polished alloy rims with stainless steel spokes (22" frame has 28" rims). Tyres 26x1 3/8" Schwalbe Marathon Plus tyres (22" frame has 28 x1 1/2" tyres) with extra SmartGuard puncture protection and reflective side walls. Mud ards Classic rofile steel uards with hand</p>		Pieces	200	
---	---	--	--------	-----	--

applied gold lining and rear reflector. Pedals Alloy body with non-slip rubber inserts. Crankset Traditional, slender chromed steel cranks. Frame Size 17.5", 20" or 22" (see sizing)				
Total				

Requested by Males Emmanuel Signature  Date 13th July 2021

Approved By Florence Baya Signature  Date 13/07/2021
(Country Representative/Finance and Admin Director)

For Procurement Department Use Only

Date Received	Reviewed By	Requisition No.
Approved By (Optional):		Date:



Figure 1. HONDA XL 125 on & OffRoad



Figure 2 Bicycle Princes Severance Classic