

PRODUCT SPECIFICATION - JX75T 4 WD		
MODEL	CASE IH JX75T	
ORIGIN	India	
DESC.	4WD / ROPS & Canopy	
ENGINE:		
Made/Model/Emission	IVECO / S8000 / TIER I	
No. of cylinders/aspiration	4/Turbocharge	
Capacity (cm3)	3908	
Rated horsepower (kW/hp)	55/75	
Rated engine speed (rpm)	2500	
Max. torque (Nm)	290@1400 rpm	
Injection pump type/make	Mechanical	
Air filter	Dry with pre cleaner	
Fuel filter	Dual spin on with water seperator	
Fuel tank capacity (L)	63	
РТО	Mechanical 540 rpm	
HYDRAULICS & REAR LINKAGE:		
Main pump flow (I/min)	34	
Number of remote valves	2 Convertible single/double acting	
Rear linkage Category, Type	I/II, 3 Point Linkage HD Type	
Draft control	Mechanical/position, draft,mixed & lift O Matic	
Max. lift capacity (kg)	1920@ball ends	
AXLES	4WD front axle / Outboard reduction with wet brakes rear axle	
HITCHES & DRAWBARS	Swinging Drawbar	
MISCELLANEOUS	Tool box & Set of tools	
DIMENSIONS & WEIGHT:		
Overall length w frt weights/width (mm)	3810	
Top of ROPS (mm)	2475	
Wheel base (mm)	2160	
Weight without ballast (kg)	2730	

Group 105	
Remotes	1 RMT SDA
Gearbox	8+2 Partial Synchromesh

Wheels 01	
Front	12.4-24 6 PR
Rear	18.4 - 30 10PR